

Appl. No. 09/314,615  
Reply to Final Office Action of April 21, 2004

**Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1-13 (canceled)

Claim 14 (currently amended): A method of managing audio transducers, comprising:

receiving a configuration for a plurality of audio transducers, said configuration specifying that audio signals are to be sent to a first audio transducer and received from a second audio transducer;

detecting that a third audio transducer has been turned on;

storing the configuration for the plurality of transducers, said stored configuration specifying that audio signals are to be sent to a first audio transducer and received from a second audio transducer;

changing the configuration such that audio signals are sent to the third audio transducer instead of the first audio transducer; and

changing the configuration such that audio signals are received from the third audio transducer instead of the second audio transducer.

Claim 15 (canceled)

Claim 16 (currently amended): The method of claim 14, further comprising:

detecting that the third audio transducer has been turned off; and

restoring the configuration to said stored configuration such that audio signals are sent to the first audio transducer instead of the third audio transducer.

Claim 17 (original): The method of claim 14, further comprising setting the configuration in an audio device between the plurality of audio transducers and a computer system, wherein said configuration is received from the computer system.

Appl. No. 09/314,615  
Reply to Final Office Action of April 21, 2004

Claim 18 (original): The method of claim 17, wherein the configuration is input by a user utilizing a graphical user interface (GUI).

Claim 19 (original): The method of claim 18, further comprising:  
allowing a user to select one of an input or output audio transducer; and  
automatically selecting a default corresponding input or output audio transducer according to the user's selection.

Claim 20 (original): The method of claim 14, wherein the third audio transducer is a telephony device and is turned on by going off hook.

Claim 21 (original): The method of claim 14, further comprising setting the configuration in an audio device coupled to the plurality of audio transducers, said audio device being a sound card.

Claim 22 (new): A method of managing audio transducers, comprising:  
displaying a configuration for a plurality of audio transducers;  
receiving a user selection of an audio transducer, the user selection indicating that the selected audio transducer is to be utilized;  
determining if there is a default audio transducer that corresponds to the selected audio transducer;  
automatically selecting the default audio transducer so that it is to be utilized if it is determined there is a default audio transducer that corresponds to the selected audio transducer; and  
sending the configuration to an audio transducer switch.

Claim 23 (new): The method of claim 22, further comprising receiving user input that specifies an audio transducer that corresponds to another audio transducer as a default.

Claim 24 (new): The method of claim 22, wherein the selected audio transducer is an input audio transducer and the default audio transducer is an output audio transducer.

Appl. No. 09/314,615  
Reply to Final Office Action of April 21, 2004

**Claim 25 (new):** The method of claim 22, wherein the selected audio transducer is an output audio transducer and the default audio transducer is an input audio transducer.

**Claim 26 (new):** The method of claim 22, wherein the configuration for the plurality of audio transducers that is displayed is a default audio configuration.

**Claim 27 (new):** The method of claim 22, further comprising storing the configuration for the plurality of audio transducers.

**Claim 28 (new):** The method of claim 22, wherein the user selection is made in a graphical user interface.